

M A P

Application Solutions

Stainless Steel Air Filters

Background

Harsh Environments can lead to problems with the reliability, integrity, and maintenance of process components. Facility equipment and components can be subjected to accelerated corrosion leading to short service life and frequent maintenance. This results in high maintenance costs, replacement costs, and unpredictable production downtime. To minimize these high costs, the equipment and components are typically constructed of stainless steel which will hold up against chemical and vapor attack.

Application

Chemical plants, refineries, pulp and paper mills, food processing plants and other industries all have production areas located in aggressive ambient environments. These areas typically house pneumatically operated production equipment that require clean, dry compressed air. Until recently, most facilities have used compressed air filter

Case Study

A large national food processor had been using anodized aluminum filter assemblies in compressed air lines supplying critical production equipment. This area required nightly wash downs with aggressive chemicals necessary to sterilize the production area. Under these conditions the anodized aluminum filter assemblies would last approximately one year before requiring replacement. Chemical attack and corrosion rendered them unsafe for use. Recently, this food processor replaced the aluminum filter assemblies with the Balston 6000



assemblies constructed of anodized aluminum or other light metal to filter the compressed air. These materials are very susceptible to corrosion resulting in difficult maintenance and premature failure. The Balston 6000 Series are constructed of 304 stainless steel designed to hold up to the harshest environments for many years of trouble free service.

Series stainless steel filters. The 304 stainless construction is ideal for holding up against these aggressive wash down chemicals and as a result have shown no sign of corrosion or chemical attack. This food processor uses all the Balston grades of filtration throughout its facility, from standard pneumatic quality air for processing equipment, to sterile air for food packaging. They continue to add more Balston filters for all their new production areas.

Solutions

Features and Benefits

- Removes all viable organisms
- Removes all moisture and particulate contamination
- Has full compliance with FDA requirements
- Able to meet the flows of a variety of applications
- In full compliance with USDA requirements
- Stainless steel housing

Principal Specifications

Principal Specifications				
Model	6002	6004	6006	6008
Port Size	1/4" NPT	1/2" NPT	3/4" NPT	1" NPT
Materials of Construction				
Head	304 Stainless Steel	→	→	→
Bowl	304 Stainless Steel	→	→	→
Internals	Nylon	Nylon	Stainless Steel	Stainless Steel
Seals	Buna-N Food Grade	→	→	→
Maximum Temperature (1)	120°F (49°C)	→	→	→
Maximum Pressure (2)	175 psig	→	→	→
Minimum Pressure (3)	15 psig	→	→	→
Shipping Weight	3.5 lbs.	4.0 lbs.	11 lbs.	12 lbs.
Dimensions	3"W X 7"L (7mm X 18mm)	3"W X 10"L (7mm X 25mm)	4"W X 10"L (10mm X 25mm)	4"W X 12"L (10mm X 30mm)

1 Max. temperature with auto drain. Max. temperature with manual drain is 275°F.

2 Max. pressure with auto drain. Max. pressure with manual drain is 250 psi.

3 Required for proper operation of auto drain.

Ordering Information For assistance, call toll-free at 1-800-343-4048 8AM to 5PM Eastern Time

Assembly Ordering Information (4)				
Model P/N	Filter Tube	Drain (Manual)	Drain (Auto. Float)	Mounting Bracket
6002N-0A2-(?X)	100-12-(?X)	A03-0178	N/A	C01-0094
6002N-0A1-(?X)	100-12-(?X)	N/A	A03-0179	C01-0094
6002N-0A2-SA	100-12-SA	A03-0178	N/A	C01-0094
6002N-0A2-000	100-12-000	A03-0178	N/A	C01-0094
6004N-0A2-(?X)	100-18-(?X)	A03-0178	N/A	C01-0094
6004N-0A1-(?X)	100-18-(?X)	N/A	A03-0179	C01-0094
6004N-0A2-SA	100-18-SA	A03-0178	N/A	C01-0094
6004N-0A2-000	100-18-000	A03-0178	N/A	C01-0094
6006N-0A2-(?X)	200-176-(?X)	A03-0178	N/A	C01-0094
6006N-0A1-(?X)	200-176-(?X)	N/A	A03-0179	C01-0094
6006N-0A2-SA	200-176-SA	A03-0178	N/A	C01-0094
6006N-0A2-000	200-176-000	A03-0178	N/A	C01-0094
6008N-0A2-(?X)	200-185-(?X)	A03-0178	N/A	C01-0094
6008N-0A1-(?X)	200-185-(?X)	N/A	A03-0179	C01-0094
6008N-0A2-SA	200-185-SA	A03-0178	N/A	C01-0094
6008N-0A2-000	200-185-000	A03-0178	N/A	C01-0094
Replacement Filter Cartridge Ordering Information				
Model P/N	6002	6004	6006	6008
Replacement Filter Cartridges				
Number required	1	1	1	1
Box of 5	5/100-12-(?X)	5/100-18-(?X)	5/200-176-(?X)	5/200-185-(?X)
Box of 10	100-12-(?X)	100-18-(?X)	200-176-(?X)	200-185-(?X)
Box of 10	100-12-SA	100-18-SA	200-176-SA	200-185-SA
CI Cartridges (box of 1)	C1100-12-000	C1100-18-000	C1200-176-000	C1200-185-000



Parker Hannifin Corporation
 Filtration and Separation Division
 242 Neck Road, P.O. Box 8223
 Haverhill, MA 01835-0723
 Phone: 800-343-4048 or 978-858-0505
 Fax: 978-556-7501
www.parker.com/balston

MAP Stainless Steel Air Filters-A
 Reprinted in U.S.A. March 2008

Copyright © Parker Hannifin Corporation 2006, 2008